





With outstanding performance, ergonomic design and optimum functionality

GS550 meets the demands of wide variety of applications



Read both 1D and 2D barcodes on paper or even on electronic screen



Supports both handheld and presentation scanning mode with automatic object detection and scanning



Equipped with cutting-edge decoding technology for fast and accurate scanning



Stylish scanner holder as optional accessory

G\$550 2D Imager Scanner

Model	G\$550U	G\$550K
System Interface	USB 2.0	Keyboard Wedge
Scan Pattern	Area Image (640 x 480 pixel array)	
Motion Tolerance	Up to 10 cm/s (4 in/s) for 13 mil UPC at optimal focus	
Scan Angle	Horizontal 42.4°; Vertical: 30.8°	
Symbol Contrast	35% minimum reflectance difference	
Pitch, Skew	60°, 70°	
Decode Capabilities	Aztec, China Post (Hong Kong 2 of 5), Chinese Sensible (Han Xin) Code, Codabar, Codablock A & F, Code 128, Code 39, Code 93, Data Matrix, EAN/JAN-13, EAN/JAN-8, G\$1 Composite Codes, G\$1 DataBar Expanded, G\$1 DataBar Limited, G\$1 DataBar Omnidirectional, G\$1 Emulation, G\$1-128, Interleaved 2 of 5, Korea Post, Matrix 2 of 5, MicroPDF417, M\$1, NEC 2 of 5, Postal Codes-Linear, PDF417, QR Code, Straight 2 of 5 IATA (two-bar start/stop), Straight 2 of 5 Industrial (two-bar start/stop), TCIF Linked Code 39 (TLC39), UPC-A, UPC-A/EAN-13 with Extended Coupon Code, UPC-E0 and UPC-E1	
Input Voltage	4.0V DC to 5.0V DC	
Power	2 W (400mA @ 5V DC - Operating) 0.45 W (90mA @ 5V DC - Standby)	
Agency Approvals	CE, FCC, BSMI	
Environment	Operating Temperature: 32°F to 104°F (0°C to 40°C) Storage Temperature: -40°F to 140°F (-40°C to 60°C)	
Humidity	0% to 95% relative humidity, non-condensing	
Light Levels	0 to 100,000 lux (9,290 foot-candles)	
IP Rating	Intrusion Protection, IP42 requirement for case design	
Drop	Designed to withstand 1m drops	
Dimension	Length: 4.33" (110 mm) Height: 6.02" (153 mm) Width: 2.76" (70 mm)	
Weight	0.27 lbs (0.12Kg)	
Color	Black & Orange White & Red	



^{*} Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

Re 2.2 2012/11/1



Godex International (Headquarters) Telephone: +886 2 2225 8580

Godex Americas Telephone: +1 805 987 5100

Godex China Telephone: +86 21 56651313 Godex Europe

Telephone: +49 2193 53396 0